



**CATHODIC UNI-SET INSULATION KIT**  
**Double Washer**  
**Raised Face (Type F)**  
**ASME B 16.5**

N.P.S.	150 lb	300 lb	400 lb	600 lb	900 lb	1500 lb	2500 lb
1/2	7.27	7.43	7.49	7.49	9.64	9.64	9.99
3/4	7.27	7.43	7.49	7.49	9.64	9.64	9.99
1	7.27	7.43	7.49	7.49	9.64	9.64	9.99
1 1/4	7.43	7.47	7.76	7.75	9.81	9.81	12.38
1 1/2	7.72	8.43	8.83	8.83	12.05	12.05	13.90
2	7.92	12.05	14.66	14.72	20.42	20.42	24.91
2 1/2	8.47	15.88	16.73	16.88	25.25	25.25	28.47
3	8.77	16.77	17.77	17.78	26.87	27.93	33.71
4	15.60	17.88	20.60	21.95	28.53	33.00	45.02
5	17.30	19.45	22.24	28.55	34.28	45.63	-
6	18.25	28.49	33.09	41.30	47.39	60.22	-
8	20.77	34.32	42.17	47.85	62.74	-	-
10	32.10	52.49	60.12	74.62	85.65	-	-
12	37.68	61.23	70.25	91.92	110.54	-	-
14	45.64	81.05	89.51	102.01	124.26	-	-
16	59.59	89.93	103.54	123.51	-	-	-
18	62.85	109.28	122.13	-	-	-	-
20	76.72	115.59	140.83	-	-	-	-
24	97.74	154.48	-	-	-	-	-